



△ SPECIFICATION:

Material : Post :Brass,Tin-Plated
 Base : Nylon 46 UL 94V-0
 Voltage Rating : AC 100V DC
 Current Rating : AC DC 2A
 Withstanding Voltage : AC 800V/Min
 Insulation Resistance : 1000Megohms Min
 Temperature range : -25°C to 85°C
 Contact Resistance : Initial Value/10 Milliohms Max
 After Environmental Testing /20 Milliohms Max.

Poles	Dimension : mm		
	A	B	C
2	2.0	7.95	4.60
3	4.0	9.95	6.60
4	6.0	11.95	8.60
5	8.0	13.95	10.60
6	10.0	15.95	12.60
7	12.0	17.95	14.60
8	14.0	19.95	16.60
9	16.0	21.95	18.60
10	18.0	23.95	20.60
11	20.0	25.95	22.60
12	22.0	27.95	24.60
13	24.0	29.95	26.60
14	26.0	31.95	28.60
15	28.0	33.95	30.60
16	30.0	35.95	32.60

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

15767

APPROVED BY

MEI

CHECKED BY

LHC

DRAWING BY

HZF

SCALE

NONE

REV.

A2

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 .X ±0.35 △
 .XX ±0.25 △
 ANG.

UNIT mm



NO.	REV.	REVISIONS	CHK	DATE
△ A2		Add Dim.	BECKY	2004/09/21
△ A1		Modify Tolerances. & Add Drawing	BECKY	2004/09/20
△ A1		Modify & Del Spec.	BECKY	2004/09/20
△ A		NEW RELEASE		